

erebus



Features:

- 5 Year Electrical System Warranty
- High Colour Consistency (MacAdam 3 SDCM)
- Interchangeable Zhaga LED Modules
- IES Files Available
- Passive Cooling
- Dimmable
- CRI > 80/90/98

Architectural Semi-Recessed LED Down Light

LED options

3000K and 4000K - CRI > 80/90/98

Lumiled Modules

Trim Finish

White and Black Die Cast Aluminium

Safety Glass


Clear

Control Equipment


Switched, DALI and Phase Cut

Optics


Narrow (20 deg) Medium (40 deg) Wide (60 deg)



Erebus 6/10S



Erebus 17/25M



Erebus 38L

Lumen Output*		CRI80 - 3000k			CRI80 - 4000k			CRI90 - 3000k			CRI90 - 4000k			CRI98 - 3000k		
Type**	Power (W)	20°	40°	60°	20°	40°	60°	20°	40°	60°	20°	40°	60°	20°	40°	60°
6S	6 watts	610	610	610	660	660	660	510	510	510	560	560	560	450	450	450
10S	10 watts	800	800	800	900	900	900	685	685	685	770	770	770	600	600	600
17M	17 watts	1900	1900	1900	2100	2100	2100	1520	1520	1520	1790	1790	1790	1700	1700	1700
25M	25 watts	2550	2550	2550	2840	2840	2840	2050	2050	2050	2400	2400	2400	2000	2000	2000
38L	38 watts	3600	3600	3600	4000	4000	4000	2900	2900	2900	3400	3400	3400	2750	2750	2750

*All lumen output data based on LED tp/tc point at 65°C ** S = Small Body M = Medium Body L = Large Body

PRODUCT CODE BUILDER

EREBUS6S - 3080 - C - W - R - N - S

Wattage

- 6W - EREBUS6S
- 10W - EREBUS10S
- 17W - EREBUS17M
- 25W - EREBUS25M
- 38W - EREBUS38L

LED Colour/Index

- 3000K CRI80 - 3080
- 3000K CRI90 - 3090
- 3000K CRI98 - 3098
- 4000K CRI80 - 4080
- 4000K CRI90 - 4090

Diffuser

- Clear - C

Trim Finish

- White - W
- Black - B

Mounting

- Recessed - R

Optics

- Narrow - N
- Medium - M
- Wide - W

Control

- Switched - S
- DALI - D
- Phase Cut - P

Xulux Pty Ltd
 14/388 Newman Road Geebung Qld 4034
 P 07 3172 7131 F 07 3161 5598
 E sales@xulux.com.au
 W www.xulux.com.au

Specifications are subject to change without notice
 EREBUSRX2

