



Features:

- 5 Year Electrical System Warranty
- High Colour Consistency (MacAdam 3 SDCM)
- Interchangeable Zhaga LED Modules
- IES Files Available
- Passive Cooling
- Dimmable
- CRI > 80

Architectural Fixed LED Down Light

LED options

3000K and 4000K - CRI > 80

Lumiled Modules

Trim Finish

White and Black Die Cast Aluminium

Safety Glass


Clear

Control Equipment


Switched, DALI and Phase Cut

Optics


Wide (60 deg)



Heos 13S



Heos 21/30M



Heos 30/40L

Lumen Output*		CRI80 - 3000k	CRI80 - 4000k	Type	Cutout Ø mm	Type	Weight KG
Type**	Power (W)	60°	60°				
13S	13 watts	1000	1191	13S	90-95	13S	0.2
21M	21 watts	1518	1817	21M	170-180	21M	0.9
30M	30 watts	2034	2155	30M	170-180	30M	0.9
30L	30 watts	2069	2175	30L	210-220	30L	1.3
40L	40 watts	3401	3570	40L	210-220	40L	1.3

*All lumen output data based on LED tp/tc point at 65°C ** S = Small Body M = Medium Body L = Large Body

PRODUCT CODE BUILDER

HEOS13S - 3080 - C - W - R - W - S

Wattage

13W - HEOS13S
21W - HEOS21M
30W - HEOS30M
30W - HEOS30L
40W - HEOS40L

LED Colour

3000K CRI80 - 3080
4000K CRI80 - 4080

Diffuser

Clear - C

Trim Finish

White - W
Black - B

Mounting

Recessed - R

Optics

Wide - W

Control

Switched - S
DALI - D
Phase Cut - P