

quadra



Features:

- 5 Year Electrical System Warranty
- High Colour Consistency (MacAdam 3 SDCM)
- Interchangeable Zhaga LED Modules
- IES Files Available
- Passive Cooling
- Dimmable
- Tiltable - 20 Degrees
- CRI > 80

Architectural Adjustable Square LED Down Light

LED options

3000K and 4000K - CRI > 80
Lumiled Modules

Trim Finish

White and Black Die Cast Aluminium

Safety Glass


Clear

Control Equipment


Switched, DALI and Phase Cut

Optics


Narrow (20 deg) Medium (40 deg)



Quadra 1L30/40



Quadra 2L30/40



Quadra 3L30/40

Lumen Output*		CRI80 - 3000k		CRI80 - 4000k	
Type**	Power (W)	20°	40°	20°	40°
1L30	1 x 30 watts	2174	2129	2304	2257
1L40	1 x 40 watts	3604	3440	3820	3646
2L30	2 x 30 watts	2 x 2174	2 x 2129	2 x 2304	2 x 2257
2L40	2 x 40 watts	2 x 3604	2 x 3440	2 x 3820	2 x 3646
3L30	3 x 30 watts	3 x 2174	3 x 2129	3 x 2304	3 x 2257
3L40	3 x 40 watts	3 x 3604	3 x 3440	3 x 3820	3 x 3646

*All lumen output data based on LED tp/tc point at 65°C ** S = Small Body M = Medium Body L = Large Body

PRODUCT CODE BUILDER

QUADRA1L30 - 3080 - C - W - R - N - S

Wattage

30W - **QUADRA1L30**
40W - **QUADRA1L40**
60W - **QUADRA2L30**
80W - **QUADRA2L40**
90W - **QUADRA3L30**
120W - **QUADRA3L40**

LED Colour/Index

3000K CRI80 - **3080**
4000K CRI80 - **4080**

Diffuser

Clear - **C**

Trim Finish

White - **W**
Black - **B**

Mounting

Recessed - **R**

Optics

Narrow - **N**
Medium - **M**

Control

Switched - **S**
DALI - **D**
Phase Cut - **P**

XULUX Pty Ltd
14/388 Newman Road Geebung Qld 4034
P 07 3172 7131 F 07 3161 5598
E sales@xulux.com.au
W www.xulux.com.au

Specifications are subject to change without notice
QUADRARX2

